

CMPPro High Intensity Discharge Floodlight

Product Introduction

Housing

Deep drawn steel housing; Tool-less design; Type 316 Stainless Steel

Wind Rating

EPA-3.62 / 5.39 at vertical

Lens

Tempered Glass

Lamp Holder

E40

Ballast

Magnetic Ballast in separate ballast Box, IP66(1000W)
Magnetic Ballast in housing (250/400W)

Application Area

IP66, for engine room, up-deck, or other watertight required spaces

Lamp

250W, 400W, 1000W HID

Mounting

Stainless steel mounting brackets, see "Dimension" for detail

Entries

Two M25 brass cable glands

Terminal Block

3 pole 6mm² max

Ambient Temp

Standard: -25 °C~+55 °C



Ordering Information

CMPPro	-02	-225
	02-250W	225-220V 50Hz
	04-400W	226-220V 60Hz
	10-1000W	235-230V 50Hz
		236-230V 60Hz
		245-240V 50Hz
		246-240V 60Hz

Commonly Ordered Luminaires

Wattage	Volt/Fre	Description	Material code	Weight kg
250W	220V 50Hz	CMPPro-02-225	CCL1209636	21
	230V 60Hz	CMPPro-02-236	CCL1209639	
400W	220V 50Hz	CMPPro-04-225	CCL1209642	21
	230V 60Hz	CMPPro-04-236	CCL1209645	
1000W	220V 50Hz	CMPPro-10-225	CCL1209347	40
	230V 60Hz	CMPPro-10-236	CCL1209350	

Please consult Eaton's Crouse-Hinds for more configurations!

Dimensions

