

ADE 1a

Product Introduction

Type of Cable Gland

- With elastomeric seal

Cable type

- Non-armoured cable

Certifications

- IP66

Features:

- Standard nickel-plated brass material for superior corrosion resistance.
- Neoprene seal certified from -40°C~100°C.

Caution: A cable clamping must be realized within a range of 300mm from the extremity of the cable gland.



EXAMPLE		OPTIONS (required)	
CAP81669 4A		9F stainless steel 304**	
		4A nickel-plated brass	
Gland Type	Options		

Gland Size	Thread Size		Length 'E' (mm)	Cable Outer Sheath (mm)	Gland Length 'L' (mm)	Hexagone	
	ISO	Reference				'A'* (mm)	'B'* (mm)
4	16	CAP816594A	15	4.5-8.5	20	15	19
5		CAP816504A	15	7-12	22	19	19
4	20	CAP816674A	15	4.5-8.5	20	15	24
5		CAP816694A	15	7-12	22	19	24
6		CAP816604A	15	10-16(15.5)	25	24	24
5	25	CAP816774A	15	7-12	22	19	30
6		CAP816794A	15	10-16	25	24	30
7		CAP816704A	15	13.5-20.5(21)	27	30	30
7	32	CAP816894A	15	13.5-21	27	30	41
8		CAP816804A	15	18-27.5	34	41	41
8	40	CAP816994A	15	18-27.5	34	41	48
9		CAP816904A	15	23-34	36	48	48
9	50	CAP817094A	15	23-34	36	48	55
10		CAP817004A	15	29-41	39	55	55
11	63	CAP817294A	17	35-48	41	64	64
12		CAP817204A	17	42-56	43	72	72

* A, B is the parallel-edge distance of Hexagon, and the diagonal-edge distance is Ax1.1, Bx1.1.

** Please use lube in the fastening operation of stainless steel products against thread seizure. Please find the detailed lube information in accessories.